

NiCd Production Safety Data Sheet

Producer Name: Aria Industrial Co., Ltd

Model : 110232-A

Designed for Recharge: Yes

MSD Ref. No.: Aria-2024 M209

SECTION I-MANUFACTURER INFORMATION

Aria Industrial Co., Ltd.
Baisha Industrial Development Area
Western Area, Jiangmen,
GuangDong, P. R. China
Telephone Number for Information: 86-750-3530999

SECTION II-HAZARDOUS INGREDIENTS

IMPORTANT NOTE:

The battery should not be opened or burned. Exposure to the ingredients contained within or their combustion products could be harmful.

| MATERIAL OR INGREDIENTS | % W. t. |
|---|----------|
| Cadmium as cadmium metal cadmium oxide cadmium hydroxide | 8-22 |
| Cobalt as cobalt metal cobalt oxide cobalt hydroxide | 1-2 |
| Nickel as nickel metal nickel oxide nickel hydroxide | 20-30 |
| Mercury | 0-0.0005 |
| Lead as lead metal lead oxide | 0-0.004 |
| Potassium Hydroxide | 0-5 |

SECTION III – FIRE AND EXPLOSION HAZARD DATA

If fire or explosion occurs when batteries are on charge, shut off power to charge.

In case of fire, it is permissible to use any class of extinguishing medium on these batteries or their packing materials. Cool exterior of batteries if exposed to fire to prevent rupture.

Fire fighters should wear self-contained breathing apparatus. Nickel-Cadmium batteries involved in a fire can vent and produce toxic fumes including nickel, nickel oxide, cadmium, cadmium oxides, and cobalt oxides.

SECTION IV- HEALTH HAZARD DATA

Under normal conditions of use, the battery is hermetically sealed.

Ingestion:

Swallowing a battery can be harmful.

Contents of an open battery can cause serious chemical burns of mouth, esophagus, and gastrointestinal tract. Contents include toxic cadmium compounds that can cause excessive salivation, choking, nausea, persistent vomiting, diarrhea, abdominal pain, dizziness, faintness, unconsciousness, and possible liver and kidney injury.

If a battery or open battery is ingested, do not induce vomiting or give food or drink. Seek medical attention immediately.

Inhalation:

Contents of an open battery can cause respiratory irritation. Cadmium oxide fumes and cause metal fume fever. Hypersensitivity to nickel can cause allergic pulmonary asthma. Provide fresh air and seek medical attention.

Skin Contact:

Contents of an open battery can cause skin irritation and/or chemical burns. Cobalt, cobalt compounds, nickel, and nickel compounds can cause skin sensitization and an allergic contact dermatitis. Remove contaminated clothing and wash skin with soap and water. If a chemical burn occurs or if irritation persists, seek medical attention.

Eye Contact:

Contents of an open battery can cause severe irritation and chemical burns. Immediately flush eyes thoroughly with water for at least 15 minutes, lifting upper and lower lids, until no evidence of the chemical remains. Seek medical attention.

SECTION V: PRECAUTIONS FOR SAFE HANDLING AND USE**Storage:**

Store in a cool, well-ventilated area. Elevated temperature can result in shortened battery life.

Mechanical Containment:

Do not obstruct safety release vents on batteries. Encapsulation of batteries will not allow cell venting and can cause high-pressure rupture.

Handling:

Accidental short circuit for a few seconds will not seriously affect the battery. However, this battery is capable of delivering very high short circuits. Prolonged short circuits will cause high cell temperatures that can cause skin burns. Sources of short circuits include jumbled batteries in bulk containers, metal jewelry, and metal covered tables or metal belts used for assembly of batteries into devices.

If soldering or welding to the battery is required, use of tabbed batteries is recommended.

Do not open battery. The negative electrode material maybe pyrophoric. Should an individual cell from a battery become disassembled, spontaneous combustion of the negative electrode is possible. That is much more like to happen if the electrode is removed from its metal container. There can be a delay between exposure to air and spontaneous combustion.

Charging:

This battery is made to be charging many times. Because it gradually loses its charge over a few months, it is good practice to charge battery before use. Use recommended charger. Improper charging can cause heat damage or even high pressure rupture. Observe proper charging polarity.

SECTION VI-SPECIAL PROTECTION INFORMATION**Ventilation Requirements:**

Not necessary under normal conditions.

Respiratory Protection:

Not necessary under normal conditions.

Eye Protection:

Not necessary under normal conditions. Wear safety glasses with side shields if handling an open or leaking battery.

Glove:

Not necessary under normal conditions. Use neoprene or natural rubber gloves if handling an open or leaking battery.

Open Battery Storage:

Battery should not be opened. Should a cell become disassembled, the electrode should be stored in a fireproof cabinet, away from combustibles.

SECTION VII-DISPOSAL METHOD

Dispose of batteries according to government regulations.

SECTION VIII-TRANSPORTATION INFORMATION

-IATA Dangerous Goods Regulations 65th Edition(2024)

TRANSPORT INFORMATION

This battery doesn't correspond to dangerous article of the United Nations transportation regulations.

Moreover, this article doesn't correspond to dangerous article to which transportation is restricted by the following decree and guideline.

TECHNICAL INSTRUCTIONS FOR THE SAFE TRANSPORT OF DANGEROUS GOODS BY AIR(ICAO)

IATA Dangerous Goods Regulations(IATA)

INTERNATIONAL MARITIME DANGEROUS GOODS CODE(IMO)

Code of federal regulations(U.S.DOT)

However, it is necessary to obey the IATA Dangerous Goods Regulations(A123).

In the case of transportation, confirm no leakage and no spillage from a container, Take in a cargo of them without falling, dropping and breakage. Prevent collapse of cargo piles and wet by rain, The container must be handled carefully. Do not give shocks that result in a mark of hitting on a cell. Take the protection measures not short-circuited.

Moreover, do not damage or remove the external tube, Never throw out cells in a fire or expose to high temperatures. Do not soak cells in water and seawater, Never disassemble, modify or deform. Avoid direct sunlight, high temperature, high humidity

SECTION IX-REGULATORY INFORMATION

Special requirement be according to the local regulatory.

SECTION X-OTHER INFORMATION

The data in this Material Safety Data Sheet relates only to the specific material designated herein.

SECTION XI-MEASURES FOR FIRE EXTINCTION

In case of fire, it is permissible to use any class of extinguishing medium on these batteries or their packing material. Cool exterior of batteries if exposed to fire to prevent rupture.

Fire fighters should wear self-contained breathing apparatus.

SECTION XII - PHYSICAL / CHEMICAL CHARACTERISTICS

| | |
|--------------------------------|---|
| Boiling Point N.A. | Specific Gravity (H ₂ O=1) N.A. |
| Vapor Pressure (mm Hg) N.A. | Melting Point N.A. |
| Vapor Density (AIR=1) N.A. | Evaporation Rate (Butyl Acetate) N.A. |
| Solubility in Water N.A. | |

| |
|--|
| Appearance and Odor Cylindrical Shape, odorless |
|--|

SECTION XIII – ACCIDENTAL RELEASE OR SPILLAGE

Steps to Be Taken in Case Material is Released or Spilled

Batteries that are leakage should be handled with rubber gloves. Avoid direct contact with electrolyte. Wear protective clothing and a positive pressure Self-Contained Breathing Apparatus (SCBA)

SECTION XIV – EXPOSURE CONTROLS / PERSON PROTECTION

| | | | |
|--|------------------------------|--------------|------|
| Occupational Exposure Limits: LTEP N.A. | | STEP N.A. | |
| Respiratory Protection (Specify Type) N.A. | | | |
| Ventilation | Local Exhausts N.A. | Special | N.A. |
| | Mechanical (General) N.A. | Other | N.A. |
| Protective Gloves N.A. | Eye Protection N.A. | | |
| Other Protective Clothing or Equipment N.A. | | | |
| Work / Hygienic Practices N.A. | | | |

SECTION XV – ECOLOGICAL INFORMATION

N.A.

SECTION XVI – REACTIVITY DATA

| | | | |
|---------------------------------------|----------------|---|---------------------|
| Stability | Unstable | | Conditions to Avoid |
| | Stable | X | |
| Incompatibility (Materials to Avoid) | | | |
| Hazardous Decomposition or Byproducts | | | |
| Hazardous Polymerization | May Occur | | Conditions to Avoid |
| | Will Not Occur | X | |